Technical data sheet

Junction box, B 11 M, with thread

Item number: 2002345





Protection rating IP54, nominal voltage 660 V, nominal cross-section 10 \div mm², two fastening holes for screws up to 6 mm Ø on the outside of the box, four cover screws, 10 break-out entries with thread M20 x 1.5, primarily for cable glands with short connecting thread.

Clear internal dimensions: 125x100x44 mm.

B 11 M empty: without earthing terminal

M CEBEC C E IP M20 mm² = 10 = 660 V

Duroplast, Aminoplast

Master data	
Item number	2002345
Type	B 11 M
Description 1	Junction box
Manufacturer	OBO
Dimension	136x111x57
Colour	Light grey; RAL 7035
Material	Duroplast, Aminoplast Typ 131.5
Smallest sales unit	1
Unit of quantity	Piece
Weight	32.2 kg
Weight unit	kg/100 pc.
CO2 Footprint (GW	P) Cradle-to- 0,6625 kg CO2e / 1 Piece

Technical data sheet

Junction box, B 11 M, with thread





Length	111 mm
Width	136 mm
Height	57 mm

Technical data

125 136

Expandable	no
No. of entries	10
Type of entry	Gland
Type of entry	Cable
Type of housing penetration	Thread and pre-marking
Measured insulation voltage Vi	660 V
Cover	Not transparent
Cover fastening	Screwed
Entry from rear	no
Entries	10 break-out entries with thread M20 x 1.5
Explosion-tested version	no
Flame-resistant	Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C
Shape	Rectangular
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
for pipe diameter	20 mm
Halogen-free	yes
Clear internal dimensions	125x100x44 mm
With screening	no
with lid	yes
Nominal cross-section, min.	10 mm ²
Nominal voltage	660 V
Sealable	yes
Impact-resistant	no
Protection rating	IP54
Transparent lid	no
Weatherproof	no