## **Technical data sheet**

### Junction box B 9 T, perforation membrane, with cable gland, PG

**Item number: 2001829** 





B9/T...: Comprises 2 halogen-free plastics components, 8 threaded entries (PG16) with push-through membrane (for cable diameter up to 15 mm)

including one in base. Where cable glands are used (giving additional strain

relief) there is no need to remove the membrane (this saves time).

Protection IP67. Rated voltage 400 V; Nominal cross section 4 ÷ 6 mm². The lid is secured with 4 pre-fitted rapid fixings (180°). The fixing holes are additionally moulded with a soft plastics component for screw ø 5 mm (spacing 75 mm).

Clear internal dimensions: 98x98x40

2 fastening screw caps, 1 fastening screw plug and 3 cable glands V-TEC/KA Pg  $\,$ 



















Polypropylene

### Master data

Item number	2001829
Type	B 9 T NL
Description 1	Junction box
Description 2	with 3 cable glands
Manufacturer	OBO
Dimension	110x110x50
Colour	Light grey; RAL 7035
Material	Polypropylene
Smallest sales unit	5
Unit of quantity	Piece
Weight	17.1 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	0,7247 kg CO2e / 1 Piece


# **Technical data sheet**

# Junction box B 9 T, perforation membrane, with cable gland, PG


**Item number: 2001829** 



### Dimensions



110 mm
110 mm
51 mm



#### Technical data

Expandable	yes
No. of entries	9
Type of entry	Cable/gland
Type of entry	Cable
Type of housing penetration	Thread and sealing membrane
Measured insulation voltage Vi	400 V
Entry from rear	yes
Entries	8 threaded entries (PG16)
Explosion-tested version	no
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Halogen-free	yes
Clear internal dimensions	98x98x40 mm
Max. Conductor cross-section	6 mm <sup>2</sup>
with lid	yes
Mounting type	Wall/ceiling mounting
Nominal cross-section, max.	6 mm <sup>2</sup>
Nominal cross-section, min.	4 mm <sup>2</sup>
Nominal voltage	400 V
Sealable	yes
Protection rating	IP67
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C

# **Technical data sheet**

Junction box B 9 T, perforation membrane, with cable gland, PG

**Item number: 2001829** 



Technical data		
	Weatherproof	no