#### **Technical data sheet**

#### Junction box T350, with plug-in seal, transparent elevated cover

**Item number: 2007758** 





Junction box for the connection of cables indoors and in protected outdoor areas. Rectangular design with plug-in seals. Suitable for wall and ceiling mounting, on mounting panels and threads in the floor. With the option of fastening inside and to mount via the corner domes. High, transparent cover with quick lock, sealable. Made from halogen-free, UV-resistant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature  $650^{\circ}$ C. Impact resistance IK05 according to DIN EN 50102. Clear internal dimensions: 267x182x127 mm









Polypropylene / polycarbonate

















Item number	2007758
Туре	T 350 HD TR
Description 1	Junction box
Description 2	with high transparent cover
Manufacturer	OBO
Dimension	285x201x139
Colour	Light grey; RAL 7035
Material	Polypropylene / polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	85 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	3,2649 kg CO2e / 1 Piece

## **Technical data sheet**

# Junction box T350, with plug-in seal, transparent elevated cover





Dimensions		
	Length	285 mm
	Width	201 mm
	Height	137 mm
88 137 137		
49.5 44 49.5		
285		

		ica		

Expandable	yes
No. of entries	24
Type of entry	Plug-in seal
Type of entry	Cable
Type of housing penetration	Miscellaneous
Measured insulation voltage Vi	500 V
Equipment	Without
Cover	Transparent
Cover fastening	Screwed
Entry from rear	yes
Entries	16xM32
	8xM40
Explosion-tested version	no
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Shape	Rectangular
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Fibre-glass reinforced	yes
Halogen-free	yes
Clear internal dimensions	267x182x127 mm
With screening	no
with lid	yes
Mounting type	Wall/ceiling mounting
Nominal voltage	500 V
Sealable	yes
Protection rating	IP66
Protection rating IK code	IK05.
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Transparent lid	no

## **Technical data sheet**

Junction box T350, with plug-in seal, transparent elevated cover

**Item number: 2007758** 



Technical data		
	Weatherproof	no