## **Technical data sheet**

### Junction box T60, with plug-in seal, transparent elevated cover

**Item number: 2007750** 





Junction box for the connection of cables indoors and in protected outdoor areas. Square design with plug-in seals to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option of fastening inside and to mount via the corner domes. High, transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature  $650^{\circ}$ C. Impact resistance IK07 according to DIN EN 50102. Clear internal dimensions: 100x100x65 mm









Polypropylene / polycarbonate















Item number	2007750
Туре	T 60 HD TR
Description 1	Junction box
Description 2	with high transparent cover
Manufacturer	OBO
Dimension	114x114x76
Colour	Light grey; RAL 7035
Material	Polypropylene / polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	17.18 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	0,7896 kg COe / 1 Piece


## **Technical data sheet**

# Junction box T60, with plug-in seal, transparent elevated cover


**Item number: 2007750** 



### Dimensions



Length	114 mm
Width	114 mm
Height	74 mm



#### Technical data

· _ · · · · · · ·	
Expandable	yes
No. of entries	7
Type of entry	Plug-in seal
Type of entry	Cable
Type of housing penetration	Miscellaneous
Measured insulation voltage Vi	500 V
Equipment	Without
Cover	Transparent
Cover fastening	Screwed
Entry from rear	yes
Entries	7xM25
Explosion-tested version	no
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Shape	Square
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Halogen-free	yes
Clear internal dimensions	100x100x65 mm
With screening	no
with lid	ves
Mounting type	Wall/ceiling mounting
Nominal voltage	500 V
Sealable	ves
Protection rating	IP66
Protection rating IK code	IK07.
Permitted temperature range, max.	60 °C
max.	

## **Technical data sheet**

Junction box T60, with plug-in seal, transparent elevated cover

**Item number: 2007750** 



Technical data	
Permitted temperatur min.	re range, -5 °C
Transparent lid	yes
Weatherproof	no