

Technical data sheet

Empty housing X 06 with hat profile rail

Item number: 2005560



Junction box with hat profile rail for the connection of cables and lines indoors and in outdoor areas. Rectangular design without entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

With hat profile rail, type 2069, and fastening set.

Junction box according to EN 60670. Impact resistance IK09 according to EN 50102. Protection rating IP67 according to EN 60529.



PC

Polycarbonate

Master data		
Item number	2005560	
Type	X06C R LGR-TR	
Description 1	Empty Enclosure	
Description 2	with trans. lid, rail 2069	
Manufacturer	OBO	
Dimension	150x116x86	
Colour	Grey / transparent	
Material	Polycarbonate	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	37.6 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to-Gate	1,7376 kg CO2e / 1 Piece	


Technical data sheet

Empty housing X 06 with hat profile rail


Item number: 2005560



Dimensions



Length	151 mm
Width	117 mm
Height	86 mm



Technical data

Extension option	no
Cover fastening	Screwed
Shape	Rectangular
Suitable for outdoor use	yes
Clear internal dimensions	137x105x68 mm
with lid	yes
Mounting type	Surface-mounted
Protection rating	IP67
Protection rating IK code	IK09
Protection class	II
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Transparent lid	yes
Weatherproof	yes