Technical data sheet Empty housing X 06

Item number: 2005602





Junction box for the connection of cables and lines indoors and in outdoor areas. Rectangular design without entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogenfree and UV-resistant materials.

Junction box according to DIN EN 60670. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.



















Polycarbonate

D/I	anta:	r data
IVI	astei	uata


2005602
X06C SW
Empty Enclosure
OBO
150x116x86
Graphite black; RAL 9011
Polycarbonate
1
Piece
33.5 kg
kg/100 pc.
1,3201 kg CO2e / 1 Piece

Technical data sheet Empty housing X 06





Dimensions Length Width 117 mm Height 86 mm



Technical data

Extension option	no
Cover fastening	Screwed
Shape	Rectangular
Suitable for outdoor use	yes
Clear internal dimensions	137x105x68 mm
with lid	yes
Mounting type	Surface-mounted
Protection rating	IP67
Protection rating IK code	IK09
Protection class	II
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Weatherproof	yes