Technical data sheet

Junction box X 25

Item number: 2005074





Junction box for the connection of cables and lines indoors and in outdoor areas. Rectangular design with knock-out entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK08. Transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK08 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.

























Polycarbonate

Master data

Item number	2005074
Туре	X25 LGR-TR
Description 1	Junction box
Description 2	with transparent lid
Manufacturer	OBO
Dimension	286x202x125
Colour	Grey / transparent
Material	Polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	96.5 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	3,6355 kg CO2e / 1 Piece


Technical data sheet

Junction box X 25

Item number: 2005074



Dimensions		
25	Length	286 mm
	Width	202 mm
	Height	126 mm
<u> </u>		



32 32

Technical data

Expandable	yes	
No. of entries	10	
Type of entry	Cuttable stepped membrane	
Type of housing penetration	Pre-marking	
Measured insulation voltage Vi	750 V	
Equipment	Without	
Cover	Not transparent	
Cover fastening	Screwed	
Entry from rear	no	
Entries	10 x Ø25/40/50	
Explosion-tested version	no	
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C	
Shape	Rectangular	
Fibre-glass reinforced	yes	
Halogen-free	yes	
Clear internal dimensions	271x187x110 mm	
Max. Conductor cross-section	25 mm²	
With screening	no	
with lid	yes	
Mounting type	Wall/ceiling mounting	
Nominal cross-section, max.	25 mm²	
Nominal cross-section, min.	10 mm ²	
Nominal voltage	750 V	
Sealable	yes	
Impact-resistant	yes	
Protection rating	IP67	
Protection rating IK code	IK09	
Permitted temperature range, max.	60 °C	
Permitted temperature range, min.	-5 °C	
Transparent lid	yes	
Weatherproof	yes	